

# NPM Product Family Specifications

NPM product components include:

- Riverbed AppResponse
- Riverbed NetProfiler
- Riverbed Flow Gateway
- Riverbed NetIM
- Riverbed Portal
- Riverbed Transaction Analyzer
- Riverbed Packet Analyzer Plus

## Riverbed® AppResponse

### Model Specifications

#### AppResponse xx80 Appliances

Model	2180	4180	8180		Storage Units (for Model 8180)	
			8180	8180 Plus	48 TB Storage Unit	120 TB Storage Unit
Product SKU	SCAN-02180	SCAN-04180	SCAN-08180		SCAN-SU-4	SCAN-SU-10
Storage	12 TB raw 10 TB usable	48 TB raw 40 TB usable (RAID 0)	None		48 TB	120 TB
Supported Storage Units	N / A		1	Up to 16 <sup>5</sup>	N / A	
Maximum Storage Capacity	12 TB raw 10 TB usable	48 TB raw 40 TB usable (RAID 0)	120 TB	1.92 PB	48 TB	120 TB
Storage Disk Capacity <sup>1,2</sup>	2 x 6 TB	8 x 6 TB	N / A		12 x 4 TB	12 x 10 TB
Storage Disk Redundancy	SW RAID level 0	HW RAID 0 (default), 5, 6	N / A		HW RAID 0 (default), 5, 6 <sup>6</sup>	
Data Encryption at Rest	N / A					Yes
System and Data Capacity <sup>3,4</sup>	4 TB usable (2 x 4 TB)	8 TB usable (4 x 4 TB)	16 TB usable (8 x 4 TB)		N / A	
System and Data Disk Redundancy	Yes (RAID 10)					N / A
Operating System	Customized Linux-based OS					N / A
RAM (GB)	32	64	128		N / A	
Available Network Interface Card Slots	1	2		N / A		
Available Capture Ports	One of the following NICs: - 4 x 1 GbE Copper - 4 x 1 GbE Fiber - 2 x 10 GbE Fiber	Up to two of the following NICs: - 4 x 1 GbE Copper - 4 x 1 GbE Fiber - 2 x 10 GbE Fiber - 4 x 10 GbE Fiber	Up to two of the following NICs: - 4 x 1 GbE Copper - 4 x 1 GbE Fiber - 2 x 10 GbE Fiber - 4 x 10 GbE Fiber Or one of the following NICs: - 2 x 40 GbE Fiber	Up to two of the following NICs: - 4 x 1 GbE Copper - 4 x 1 GbE Fiber - 2 x 10 GbE Fiber - 4 x 10 GbE Fiber Or one of the following NICs: - 2 x 40 GbE Fiber - 2 x 100 GbE Fiber	N / A	
Management Port (10/100/1000 RJ45)	2					N / A

1. Raw Disk Capacity. 1 TB = 10<sup>12</sup> Bytes. It does not take into account disk formatting or RAID overhead.
2. Storage Disks store packets, and in addition can be configured to store performance metrics data.
3. Raw Disk Capacity. 1 TB = 10<sup>12</sup> Bytes. It does not take into account disk formatting or OS usage.
4. System and Data Disks store performance metrics data in addition to Operating System data.

5. All Storage Units on an individual model 8180 must be of the same capacity. With no Storage Units attached, available storage is limited to system and data capacity.
6. RAID 6 is not an option for the model 8180 when metrics priority storage mode is selected.
7. Supported inserts - 100 G Fibre ports are available with SR and LR QSFP28 inserts. 40 G Fibre ports are available with SR4, LR4, and LM4 QSFP inserts. 10 G Fibre ports are available with SR and LR SFP+ inserts (LC connectors). 1 G Fibre ports are available with SX and LX SFP inserts (LC connectors).

# Riverbed® AppResponse

## Power and Physical Specifications

### AppResponse

Model	2180	4180	8180		Storage Units (for Model 8180)	
			8180	8180 Plus	48 TB Storage Unit	120 TB Storage Unit
Product SKU	SCAN-02180	SCAN-04180	SCAN-08180		SCAN-SU-4	SCAN-SU-10
Dual Power Supplies (redundant)	✓					
Power [Watts] (typical)	132	308	408		150	170
BTU	450	1,050	1,391		512	580
Line Power Requirement	100V to 240V 50Hz to 60Hz	100V to 127V and 200V to 240V 50Hz to 60Hz			100V to 240V 50Hz to 60Hz	
Operating Temperature <sup>1</sup>	10 to 35°C (50 to 95°F)					
Humidity (shipping)	50 to 90%, non-condensing with a maximum wet bulb of 28°C (at temperatures from 25 to 35°C)					
Rack Size	1 U	2 U				
System Dimensions (LxWxH) <sup>2</sup>	645 mm (L) X 436 mm (W) X 43.6 mm (H) 25.4" (L) X 17.2" (W) X 1.72" (H)	700 mm (L) X 440 mm (W) X 87 mm (H) 27.56" (L) X 17.32" (W) X 3.43" (H)			647 mm (L) X 437 mm (W) X 89 mm (H) 25.5" (L) X 17.2" (W) X 3.5" (H)	
Packaging Dimensions (LxWxH) <sup>3</sup>	914.4 mm (L) X 609.6 mm (W) X 304.8 mm (H) 36" (L) X 24" (W) X 12" (H)				876 mm (L) X 678 mm (W) X 290 mm (H) 34.5" (L) X 26.7" (W) X 11.4" (H)	
Max Weight (without packaging) <sup>4</sup>	47 pounds	68 pounds	62 pounds		75 pounds	
Rail Information	Mounting Rail Kit Included. Orderable Spare Part Number: RMK-4-1U	Mounting Rail Kit Included. Orderable Spare Part Number: RMK-4-2U			Mounting Rail Kit Included. Orderable Spare Part Number: RMK-4-JBOD	
RoHS Compliant	✓					

1. Operating altitude up to 10,000 feet except in China 6,562 feet (2,000m).
2. Length is without bezel or cables.
3. Packaging dimensions do not include the pallet on which the unit might be shipped.

4. Weight does not include rails and front bezel.

Note: The availability, export or re-export of these products or specific features are subject to the export laws and regulations of the U.S. and the laws and regulations of any applicable foreign agency or authority.

# Riverbed® AppResponse

## Model Specifications

AppResponse Virtual					AppResponse Cloud		
Model	VSCAN-00100	VSCAN-00500	VSCAN-02000	VSCAN-FLOW	VSCAN-05000	VSCAN-AWS-SUB-010	VSCAN-AZR-SUB-010
Secondary Storage	Up to 100 GB	Up to 2 TB	Up to 8 TB	Up to 100 GB	Up to 8 TB	ST1, 7 TiB (minimum)	E60, 8 TiB (minimum)
Hypervisor	VMWare ESXi 7.0 and 8.0 Nutanix AOS 6.5.5 with AHV hypervisor Microsoft Hyper-V running on Windows Server 2019 and 2022				VMWare ESXi 7.0 and 8.0	AWS EC2	Azure Virtual Machines
vCPU	4				16	16 (c5n.4xlarge)	16 (F16s_v2)
Memory	12 GB				32 GB	42 GiB (c5n.4xlarge)	32 GiB (F16s_v2)
System Disk Space	100 GB				2 TB	2 TB	
Capture Ports	VMware: up to 8 virtual NICs or 1 physical NIC using VMDirectPath I/O passthrough <sup>2</sup> Hyper-V: up to 4 Nutanix: 1 <sup>1</sup>				VMware: up to 8 virtual NICs or 1 physical NIC using VMDirectPath I/O passthrough <sup>2</sup>	1 (shared mgmt/capture port)	
Management Ports	VMware: 2 Nutanix: 1 (shared mgmt/capture port)				2	1 (shared mgmt/capture port)	

1. On Nutanix platform, traffic is received through a VxLAN or GRE tunnel on the primary interface. There are no dedicated capture ports.
2. The following NICs are supported with VMDirectPath I/O:
  - a. Intel 82599 10 Gigabit Dual Port Network Connection
  - b. Intel Ethernet Controller X710 for 10GbE SFP+
  - c. Broadcom BCM57412 NetXtreme-E 10Gb RDMA Ethernet Controller
  - d. Intel Ethernet Controller E810-XXVDA2

# Riverbed® NetProfiler

## Product Specifications

Model	NetProfiler Supports up to 40 million de-duplicated flows per minute <sup>5</sup>		
	SCNP-04280 <sup>4,5</sup>	SCNP-04280 <sup>4,5</sup> Expansion	
	SCNP-04280	SCNP-04280-EX	SCNP-04280-DP
De-duplicated Flow Capacity (flows per minute) <sup>1</sup>	100,000 to 1,500,000		N / A
Raw Flow Capacity (flows per minute) <sup>7</sup>	7.5M		N / A
Raw Flow Capacity with Advanced Security Module (FPM) <sup>8</sup>	7.5M		N / A
Raw Disk Capacity <sup>2</sup>	52 TB		4 TB
Usable Disk Capacity <sup>3</sup>	20 TB		N / A
Optional 10 GB LAN Support <sup>7</sup>	N / A		✓
Optional Fibre Channel SAN Support <sup>6</sup>	✓		N / A
RAID	RAID 1 / RAID 10		RAID 1
Hard Disk Drives	8		2
Solid State Drives	6		N / A
RAM	256 GB		96 GB
Serial Port (DB-9)	✓		
Primary Cascade Management Port <sup>3</sup> (10/100/1000 RJ45)	✓		
Flow as Data Source <sup>9</sup>	N / A		

- Flow capacity can be expanded up to the amount listed.
- Raw Disk Capacity does not take into account disk formatting, RAID overhead, software installation, or OS usage.
- Each Flow Gateway model can report to up to two NetProfilers and forward flow to five third-party flow collectors.
- SCAN-04280-xxx and SCNP-04280-EXP equipped with RAID 10 (48 TB) and RAID10 (3.8 TB SSDs).
- Up to 32 SCNP-04280-EXP expansion modules may be added to each SCNP-04280 system. Each additional SCNP-04280-EXP enables up to 1.5M de-duplicated FPM. A maximum of 40M de-duplicated flows/min supported. SCNP-04280-DP is required with addition of sixth SCNP-04280-EXP after more than 10M FPM.

- Requires compatible SFPs.
- A flow reported by a single network interface is a raw flow. NetProfiler will de-duplicate up to 10 individual interfaces reporting the same flow into 1 de-duplicated flow.
- Disk capacity available for storage of data.
- Accepts NetFlow (V1, V5, V7, and V9), Enhanced NetFlow, IPFIX, cFlow, Cisco NBAR and NBAR2, Cisco MediaNet, Cisco ASA NSEL, Citrix AppFlow, sFlow V2 and V5, J-Flow, Packeteer FDR, Palo Alto Networks, Riverbed NPM Flow from Azure NSG Flow Logs and AWS VPS Flows.

# Riverbed® NetProfiler

## Power and Physical Specifications

Model	NetProfiler		
	SCNP-04280	SCNP-04280 Expansion	
	SCNP-04280	SCNP-04280-EX	SCNP-04280-DP
Dual Power Supplies (redundant)	✓		
Power [Watts] (typical)	268	232	
BTU	913	791	
Operating Temperature <sup>1</sup>	10 to 35°C (50 to 95°F)		
Relative Humidity (shipping)	50 to 90%, non-condensing with a maximum wet bulb of 28°C (at temperatures from 25 to 35°C)		
Rack Size	2 U	1 U	
System Dimensions (LxWxH) <sup>2</sup>	700 mm (L) x 440 mm (W) x 87 mm (H) 27.56" (L) x 17.32" (W) x 3.43" (H)	645 mm (L) x 436 mm (W) x 43.6 mm (H) 25.4" (L) x 17.2" (W) x 1.72" (H)	
Packaging Dimensions (LxWxH) <sup>3</sup>	914.4 mm (L) x 609.6 mm (W) x 304.8 mm (H) 36" (L) x 24" (W) x 12" (H)	645 mm (L) x 436 mm (W) x 43.6 mm (H) 25.4" (L) x 17.2" (W) x 1.72" (H)	
Weight (without packaging) <sup>4</sup>	61 lb	44 lb	
Rail Information	Mounting rail kit included. Orderable spare part number: RMK-4-2 U		Mounting rail kit included. Orderable spare part number: RMK-4-1 U
RoHS Compliant	✓		

1. Operating altitude up to 10,000 feet except in China 6,562 feet (2,000m).
2. Length is without bezel or cables.

3. Packaging dimensions do not include the pallet on which the unit might be shipped.
4. Weight does not include rails and front bezel.

# Riverbed® NetProfiler Virtual

## System Requirements

NetProfiler Virtual Base / Expansion  
Supports up to 40 million de-duplicated flows per minute<sup>5</sup>

Model	SCNP-VE-BASE / SCNP-VE-EXP				
De-duplicated Flow Capacity (flows per minute)	Up to 10,000	20,000 to 100,000	110,000 to 500,000	510,000 to 1,000,000	1,010,000 to 1,500,000
Raw Flow Capacity (flows per minute)	Up to 50,000	100,000 to 500,000	550,000 to 2,500,000	2,550,000 to 5,000,000	5,050,000 to 7,500,000
Hypervisor	VMWare ESXi 7.0, 8.0, Nutanix 6.5.2 LTS, and Microsoft Hyper-V 2022				
vCPU <sup>6</sup>	4 vCPUs minimum	4 vCPUs minimum / 12 vCPUs recommended	8 vCPUs minimum / 16 vCPUs recommended  2.6 GHz recommended	12 vCPUs minimum / 24 vCPUs recommended	16 vCPUs minimum / 32 vCPUs recommended
RAM	8 GB minimum / 32 GB recommended	16 GB minimum / 64 GB recommended	32 GB minimum / 96 GB recommended	64 GB minimum / 128 GB recommended	96 GB minimum / 256 GB recommended
System Disk Space	450 GB				
Flow Storage Space	500 GB minimum / 1 TB recommended	1 TB minimum / 2 TB recommended	2 TB minimum / 4 TB recommended	4 TB minimum / 10 TB recommended	5 TB minimum / 20 TB recommended
Flow Cache Space (optional) <sup>7</sup>	Not recommended (500 GB minimum)	Not recommended (500 GB minimum)	500 GB (optional)	500 GB minimum / 1 TB recommended	500 GB minimum / 2 TB recommended
Flow Storage IOPS (primary data storage)	150 minimum / 500+ recommended	500 minimum / 2,000+ recommended	1,500 minimum / 4,000+ recommended		2,000 minimum / 5,000+ recommended
Flow Cache IOPS (optional) <sup>9</sup>	300 minimum / 1,000+ recommended	1,000 minimum / 4,000+ recommended	3,000 minimum / 8,000+ recommended		4,000 minimum / 9,000+ recommended

5. Up to 32 SCNP-VE-EXP expansion modules may be added to each SCNP-BASE-VE system. Each additional SCNP-EXP-VE enables up to 1.5M de-duplicated FPM. A maximum of 40M de-duplicated flows/min is supported. SCNP-DP-VE is required after more than 10 million FPM.
6. We require this range of CPUs to be provisioned to the virtual machine, and ensure this is the number of CPU cores or threads available on the hypervisor.
7. Only provision flow cache storage if it is on separate, significantly faster datastore. Additionally, it should be only a fraction (i.e 10%) of the primary storage. Further, it should always be a smaller size than the primary flow storage, they should not be the exact same size.

8. NetProfiler support a 50 TB maximum disk volume size.
9. The optional Flow Cache disk can be used to store the most recently collected data on a faster storage tier to make reporting on the more recent data faster. We recommend provisioning SSD storage which is 10% the size of the primary flow storage.

Note: The availability, export or re-export of these products or specific features are subject to the export laws and regulations of the U.S. and the laws and regulations of any applicable foreign agency or authority.

# Riverbed® NetProfiler Virtual

## System Requirement

### NetProfiler Virtual Dispatcher

Model	SCNP-VE-DP
De-duplicated Flow Capacity (flows per minute)	0 to 40,000,000
Raw Flow Capacity (flows per minute)	0 to 150,000,000
Flow Capacity beyond which DP is required	10,000,000
Hypervisor	VMWare ESXi 7.0, 8.0, Nutanix 6.5.2 LTS, and Microsoft Hyper-V 2022
vCPU	16 vCPUs minimum / 32 vCPUs recommended 2.1 GHz minimum / 2.6 GHz recommended
RAM	32 GB minimum / 96 GB recommended
System Disk Space	120 GB

# Riverbed® NetProfiler Cloud

## Model Specifications

### NetProfiler Cloud Base/Expansion

Model	SCNP-VE / SCNP-VE-EXP			
De-duplicated Flow Capacity (flows per minute)	Up to 100,00	110,000 to 375,000	385,000 to 750,000	760,000 to 1,500,000
Raw Flow Capacity (flows per minute)	Up to 500,000	550,000 to 1,875,000	1,925,000 to 3,750,000	3,800,000 to 7,500,000
AWS Instance Type	r4.xlarge	r4.2xlarge	r4.4xlarge	r4.8xlarge
Azure Instance Type	E4s_v3	E8s_v3	E16s_v3	E32s_v3
System Disk Space	450 GB			
System Disk Type	AWS (GP2 SSD recommended), Azure (Premium SSD recommended)			
Flow Storage Space	500 GB minimum / 2 TB recommended	2 TB minimum / 4 TB recommended	4 TB minimum / 10 TB recommended	5 TB minimum / 20 TB recommended
Flow Storage Type	50 TB maximum? AWS (GP2 SSD recommended), Azure (Premium SSD recommended)			
Flow Cache Space (optional) <sup>1</sup>	Not recommended (500 GB minimum)	500 GB (optional)	500 GB minimum / 1 TB recommended	500 GB minimum / 2 TB recommended
Flow Storage Cache Type	AWS (GP2 SSD minimum/ io1 SSD recommended), Azure (Premium SSD recommended)			
Management Ports	1			

1. Only provision flow cache storage if its on a separate, significantly faster datastore. Additionally, it should only be a fraction (i.e. 10%) of the primary Flow Storage. Further, it should always be a smaller size than the primary flow storage, they should not be the exact same size.

2. While NetProfiler supports 50 TB maximum, disk volume size is limited to 16T on AWS and 32T on Azure.

# Riverbed® NetProfiler Cloud

## Model Specifications

### NetProfiler Cloud Dispatcher

Model	SCNP-VE-DP	
De-duplicated Flow Capacity (flows per minute)	0 to 10,000,000	10,010,000 to 30,000,000
Raw Flow Capacity (flows per minute)	0 to 50,000,000	50.050,000 to 150,000,000
AWS Instance Type	r4.8xlarge	
Azure Instance Type	E32s_v3	E48s_v3
System Disk Type	120GB	
System Disk Space	AWS (GP2 SSD recommended), Azure (Premium SSD recommended)	

# Riverbed® Flow Gateway

## Product Specifications

Model	Flow Gateway
	SCFG-02280 Series
De-duplicated Flow Capacity (flows per minute) <sup>1</sup>	100,000 to 8,000,000
Raw Flow Capacity (flows per minute) <sup>8</sup>	40M
Raw Flow Capacity with Advanced Security Module (FPM) <sup>8</sup>	20M
Raw Disk Capacity <sup>2</sup>	4 TB
Usable Disk Capacity <sup>2</sup>	1 TB
Optional 10 GB LAN Support <sup>7</sup>	✓
Optional Fibre Channel SAN Support <sup>7</sup>	N / A
RAID	RAID 1
Hard Disk Drives	2
Solid State Drives	N / A
RAM	64 GB
Serial Port (DB-9)	✓
Primary Cascade Management Port <sup>4</sup> (10/100/1000 RJ45)	✓
Flow as Data Source <sup>10</sup>	✓

# Riverbed® Flow Gateway

## Power and Physical Specifications

Model	Flow Gateway
	SCFG-02280 Series
Dual Power Supplies (redundant)	✓
Power [Watts] (typical)	200
BTU	682
Operating Temperature <sup>1</sup>	10 to 35°C (50 to 95°F)
Relative Humidity (shipping)	50 to 90%, non-condensing with a maximum wet bulb of 28°C (at temperatures from 25 to 35°C)
Rack Size	1 U
System Dimensions (LxWxH) <sup>2</sup>	645 mm (L) x 436 mm (W) x 43.6 mm (H) 25.4" (L) x 17.2" (W) x 1.72" (H)
Packaging Dimensions (LxWxH) <sup>3</sup>	645 mm (L) x 436 mm (W) x 43.6 mm (H) 25.4" (L) x 17.2" (W) x 1.72" (H)
Weight (without packaging) <sup>4</sup>	43 lb
Rail Information	Mounting rail kit included. Orderable spare part number: RMK-4-1 U
RoHS Compliant	✓

- Flow capacity can be expanded up to the amount listed.
- Raw Disk Capacity does not take into account disk formatting, RAID overhead, software installation, or OS usage.
- Each Flow Gateway model can report to up to two NetProfilers and forward flow to two third-party flow collectors.
- SCAN-04280-xxx and SCNP-04280-EXP equipped with RAID 10 (48 TB) and RAID10 (3.8 TB SSDs).
- Up to 32 SCNP-04280-EXP expansion modules may be added to each SCNP-04280 system. Each additional SCNP-04280-EXP enables up to 1.5M de-duplicated FPM. A maximum of 40M de-duplicated flows/min supported. SCNP-04280-DP is required with addition of sixth SCNP-04280-EXP after more than 10M FPM.

- Requires compatible SFPs.
- A flow reported by a single network interface is a raw flow. NetProfiler will de-duplicate up to 10 individual interfaces reporting the same flow into 1 de-duplicated flow.
- Disk capacity available for storage of data.
- Accepts NetFlow (V1, V5, V7, and V9), Enhanced NetFlow, IPFIX, cFlow, Cisco NBAR and NBAR2, Cisco MediaNet, Cisco ASA NSEL, Citrix AppFlow, sFlow V2 and V5, J-Flow, Packeteer FDR, Palo Alto Networks, Riverbed NPM Flow from Azure NSG Flow Logs and AWS VPC Flows.

# Riverbed® Flow Gateway Virtual

## System Requirements

### Flow Gateway Virtual

Model	SCFG-VE					
De-duplicated Flow Capacity (flows per minute)	Up to 10,000	20,000 to 100,000	110,000 to 1,000,000	1,010,000 to 2,000,000	2,010,000 to 4,000,000	4,010,000 to 8,000,000
Raw Flow Capacity (flows per minute)	Up to 50,000	100,000 to 500,000	550,000 to 5,000,000	5,050,000 to 10,000,000	10,050,000 to 20,000,000	20,050,000 to 30,000,000
Hypervisor	VMWare ESXi 7.0, 8.0, Nutanix 6.5.2 LTS, and Microsoft Hyper-V 2022					
vCPU	2 vCPUs recommended	2 vCPUs minimum / 4 vCPUs recommended	4 vCPUs minimum / 6 vCPUs recommended	6 vCPUs minimum / 8 CPUs recommended	8 vCPUs minimum / 12 vCPUs recommended	12 vCPUs minimum / 18 vCPUs recommended
	2.6 GHz recommended					
RAM	2 GB minimum / 4 GB recommended	4 GB minimum / 8 GB recommended	8 GB minimum / 16 GB recommended	16 GB minimum / 24 GB recommended	24 GB minimum / 32 GB recommended	32 GB minimum / 48 GB recommended
System Disk Space	120 GB					
Flow Storage	500 GB minimum / 2 TB maximum					
Management Ports	2					

# Riverbed® Flow Gateway Virtual

## System Requirements

### Flow Gateway Virtual with Advanced Security Module

Model	SCFG-VE					
De-duplicated Flow Capacity (flows per minute)	Up to 10,000	20,000 to 100,000	110,000 to 1,000,000	1,010,000 to 2,000,000	2,010,000 to 4,000,000	4,010,000 to 8,000,000
Raw Flow Capacity (flows per minute)	Up to 50,000	100,000 to 500,000	550,000 to 5,000,000	5,050,000 to 10,000,000	10,050,000 to 20,000,000	Up to 20,000,000
Hypervisor	VMWare ESXi 7.0, 8.0, Nutanix 6.5.2 LTS, and Microsoft Hyper-V 2022					
vCPU	4 vCPUs recommended	4 vCPUs minimum / 6 vCPUs recommended	6 vCPUs minimum / 8 vCPUs recommended	8 vCPUs minimum / 12 vCPUs recommended	12 vCPUs minimum / 16 vCPUs recommended	16 vCPUs minimum / 24 vCPUs recommended
	2.6 GHz recommended					
RAM	2 GB minimum / 4 GB recommended	4 GB minimum / 8 GB recommended	8 GB minimum / 16 GB recommended	16 GB minimum / 24 GB recommended	24 GB minimum / 32 GB recommended	32 GB minimum / 48 GB recommended
System Disk Space	120 GB					
Flow Storage	500 GB minimum / 2 TB maximum					
Management Ports	2					

# Riverbed® Flow Gateway Cloud

## Model Specifications

Model	SCFG-VE			
De-duplicated Flow Capacity (flows per minute)	Up to 100,000	110,000 to 1,000,000	1,010,000 to 3,000,000	3,010,000 to 8,000,000
Raw Flow Capacity (flows per minute)	Up to 500,000	550,000 to 5,000,000	5,050,000 to 15,000,000	15,050,000 to 30,000,000
AWS Instance Type	r4.large or m4.large	r4.xlarge or m4.xlarge	r4.2xlarge or m4.2xlarge	r4.4xlarge or m4.4xlarge
Azure Instance Type	E2s_v3 or D2s_v3	E4s_v3 or D4s_v3	E8s_v3 or D8s_v3	E16s_v3 or D16s_v3
System Disk Space	120 GB			
System Disk Type	AWS (GP2 SSD recommended), Azure (Premium SSD)			
Flow Storage	500 GB minimum / 2 TB maximum			
Flow Storage Type	AWS (GP2 SSD recommended), Azure (Premium SSD recommended)			
Management Ports	Up to 2			

# Riverbed® Flow Gateway Cloud

## Model Specifications

### Flow Gateway Cloud with Advanced Security Module

Model	SCFG-VE			
De-duplicated Flow Capacity (flows per minute)	Up to 100,000	110,000 to 1,000,000	1,010,000 to 3,000,000	3,010,000 to 8,000,000
Raw Flow Capacity (flows per minute)	Up to 500,000	550,000 to 5,000,000	5,050,000 to 10,000,000	Up to 10,000,000
AWS Instance Type	r4.xlarge	r4.2xlarge	r4.4xlarge	r4.8xlarge
Azure Instance Type	E4s_v3	E8s_v3	E16s_v3	E32s_v3
System Disk Space	120 GB			
System Disk Type	AWS (GP2 SSD recommended), Azure (Premium SSD recommended)			
Flow Storage	500 GB minimum / 2 TB maximum			
Flow Storage Type	AWS (GP2 SSD recommended), Azure (Premium SSD recommended)			
Management Ports	Up to 2			

# Riverbed® NetIM

## Model Specifications

### NetIM Manager (Virtual and Cloud Images)

Devices <sup>1</sup>	up to 1K	2.5K	5K	10K	15K	20K	25K	30K
Interface Count <sup>2</sup>	40k	100K	200K	400K	600K	800K	1M	1.2M
Polled Interface Count	20k	50K	100K	200K	300K	400K	500K	600K
vCPUs	4		6	8		10		
Memory	16 GB	20 GB	24 GB	28 GB	32 GB	40 GB	48 GB	56 GB
OS Storage	75 GB							
App Storage	500 GB	1 TB	2 TB			3 TB		
Hypervisor <sup>5,6</sup>	VMware ESXi 7.x, ESXi 8.x <sup>7</sup> , Azure Hypervisor, AWS Hypervisor, Microsoft Hyper-V 2019, Microsoft Hyper-V 2022, Nutanix AOs 6.5.2 LTS (AHV versions 20220304.342)							
Managers	1							



# Riverbed® NetIM

## Model Specifications

### NetIM Data Manager (Virtual and Cloud Images)

Devices	up to 1K	2.5K	5K	10K	15K	20K	25K	30K
Interface Count	40k	100K	200K	400K	600K	800K	1M	1.2M
Polled Interface Count	20k	50K	100K	200K	300K	400K	500K	600K
vCPUs	N / A			4				
Memory	N / A			16 GB				
OS Storage	N / A			75 GB				
App Storage	N / A			2 TB			3 TB	
Hypervisor <sup>5,6</sup>	VMware ESXi 7.x, ESXi 8.x <sup>7</sup> , Azure Hypervisor, AWS Hypervisor, Microsoft Hyper-V 2019, Microsoft Hyper-V 2022, Nutanix AOs 6.5.2 LTS (AHV versions 20220304.342)							
Data Managers <sup>3</sup>	0			1		2		3

# Riverbed® NetIM

## Model Specifications

### NetIM Worker (Virtual and Cloud Images)

Devices	up to 1K	2.5K	5K	10K	15K	20K	25K	30K
Interface Count	40k	100K	200K	400K	600K	800K	1M	1.2M
Polled Interface Count	20k	50K	100K	200K	300K	400K	500K	600K
vCPUs	4							
Memory	16 GB							
OS Storage	75 GB							
App Storage	100 GB							
Hypervisor <sup>5,6</sup>	VMware ESXi 7.x, ESXi 8.x <sup>7</sup> , Azure Hypervisor, AWS Hypervisor, Microsoft Hyper-V 2019, Microsoft Hyper-V 2022, Nutanix AOs 6.5.2 LTS (AHV versions 20220304.342)							
Workers <sup>4</sup>	1	2	4	6	8	10	12	

# Riverbed® NetIM

## Model Specifications

### NetIM Core (Virtual and Cloud Images)

Devices	up to 1K	2.5K	5K	10K	15K	20K	25K	30K
Interface Count	40K	100K	200K	400K	600K	800K	1M	1.2M
Polled Interface Count	20K	50K	100K	200K	300K	400K	500K	600K
vCPUs	4		6	8				
Memory	16 GB		32 GB	48 GB	64 GB	80 GB	96 GB	112 GB
OS Storage	75 GB							
App Storage	100 GB		200 GB	250 GB	300 GB	350 GB	400 GB	450 GB
Hypervisor <sup>5,6</sup>	VMware ESXi 7.x, ESXi 8.x <sup>7</sup> , Azure Hypervisor, AWS Hypervisor, Microsoft Hyper-V 2019, Microsoft Hyper-V 2022, Nutanix AOs 6.5.2 LTS (AHV versions 20220304.342)							
Core	1							

1. Manager and Data Manager Application Storage requirements are primarily dependent on metric retention and roll-up settings. For proof-of-concepts, the default App Storage of 100 GB may be enough if metric retention settings are reduced from the system defaults.
2. Assuming 5-minute polling and minimal latency between workers and polled elements. If CoS metrics are polled, each CoS definition applied to a polled interface counts as an additional logical interface, thereby increasing the overall polled interface count).
3. Write and query performance may improve with additional Data Manager nodes.
4. Use the netimsh "scale" command on the Manager to scale the poller and alerting services to equal the number of deployed Workers. See the NetIM Installation Guide or Upgrade Guide for instructions.

5. VMotion should be disabled for all NetIM VMs.
6. ESXi servers must be geographically collocated in the same data center for minimum latency.
7. The NetIM Virtual Appliance OVA is certified for deployment on VMware ESXi. In many cases, NetIM may be successfully deployed on other major hypervisors (i.e. KVM, AHV); however, these other hypervisors may not have been QAed or certified. Further, Riverbed maintains the right to deny support and provide support only on a best-effort basis for deployments on uncertified hypervisors.

# Riverbed® Portal

## Model Specifications

### Portal

	VMware	AWS	Azure
Product SKU	SCPRTL-FNDTN		
Hypervisor	ESXi 7.0 or 8.0 and Nutanix AOS 6.5.5 with AHV hypervisor, Microsoft Hyper-V running on Windows Server 2019 and 2022	AWS EC2	Azure Virtual Machines
vCPUs <sup>1</sup>	4	4 (c5.xlarge)	4 (Standard B4ms)
Memory	16 GB	8 GiB (c5.xlarge)	16 GiB (Standard B4ms)
OS Storage	100 GB	-	-
Instance type	-	C5.xlarge	B4MS
System Disk Space	-	100 GB	100 GB
System Disk Type	-	GP2 SSD recommended	Premium SSD recommended
Supported Browsers <sup>2</sup>	Firefox ESR 128.4.0esr, Chrome 127.0.6533.73, Edge Browser 131.0.2903.63		

1. The host CPUs must support the POPCNT CPU instructions (the Nehalem generation of Xeon CPUs (or later).
2. Internet Explorer is not supported. Other versions or browsers may or may not be compatible.

# Riverbed® Transaction Analyzer

## System Requirements

Transaction Analyzer requires, at a minimum, the following

### Transaction Analyzer

Operating Systems	Windows 10 Windows 8 (KB2883200 required for Windows 8.1) Windows Server 2012 R2 (KB2883200 also required) Windows Server 2016 Windows Server 2019
Host Hardware	x86 or EM64T (2.0 GHz or better) x86 AMD or AMD64 (2.0 GHz or better)
RAM	4 GB (recommended); 2 GB (minimum)
System File Space	5.5 GB; Up to an additional 2 GB of free disk space may be needed during installation
Working File Space	100 MB or more for temporary and log files
Display	1024 x 768 minimum resolution Video card capable of running DirectX 9
Compatible Software	Wireshark v3.27
Compatible Capture Agent Version	Version 3.10 only

Table 1 System requirement for running Transaction Analyzer.

# Riverbed® Packet Trace Warehouse

## System Requirements

Packet Trace Warehouse requires, at a minimum, the following

### Packet Trace Warehouse

Operating Systems	Windows Server 2012 R2 Windows Server 2016 Windows Server 2019
Host Hardware	x86 or EM64T (2.0 GHz or better) x86 AMD or AMD64 (2.0 GHz or better)
RAM	2 GB (recommended); 512 MB (minimum)
System File Space	20 GB (recommended); 10 GB (minimum)
Display	1280 x 1024 resolution (recommended) 1024 x 768 resolution (minimum)
Compatible Browsers	Microsoft Edge 86.0.622.38 Firefox ESR 78.3.1 Chrome 85.0.4183.121 and Chrome 86.0.4240.75.
Compatible Capture Agent Version	Version 3.10 only

Table 2 System requirement for running Packet Trace Warehouse.

# Riverbed® Capture Agents

## System Requirements

### Capture Agents

Vendor	OS	Processor
Apple	Mac OS X 10.7 – 10.13 (32 or 64-bit)	Intel
IBM	AIX 6.1 – 7.2 (64-bit)	PowerPC
Microsoft	Windows 8.1 (64-bit) & Windows 10 (64-bit) Windows Server 2012, 2016, 2019 (64-bit)	Intel, except Itanium
RedHat	RedHat Enterprise Linux 5,6,7 (32 or 64-bit)	Intel, except Itanium

Table 3 System requirements for Capture Agents.

# Riverbed® Packet Analyzer Plus

## System Requirements

Packet Analyzer Plus requires, at a minimum, the following

### Packet Analyzer Plus

Operating Systems	Microsoft Windows 8.1, 10, Server 2016 and 2019* Microsoft update <a href="https://support.microsoft.com/en-in/kb/2999226">https://support.microsoft.com/en-in/kb/2999226</a> Microsoft .NET Framework 4.6 (or later)
Suggested Hardware Platform	A Dual-core 2.0 GHz CPU or better
Memory	2 GB or more of system memory
Disk Space	300 MB of disk space for a base installation; additional space is required to store generated reports or trace files
Graphics Support	Graphics card with minimum resolution of 1024 x 768

\*Also note: Local System Live Interfaces are not supported in Windows 10 currently.

Table 4 System requirement for running Packet Analyzer Plus.



## About Riverbed

Riverbed, the leader in AI observability, helps organizations optimize their users' experiences by leveraging AI automation for the prevention, identification, and resolution of IT issues. With over 20 years of experience in data collection and AI and machine learning, Riverbed's open and AI-powered observability platform and solutions optimize digital experiences and greatly improve IT efficiency. Riverbed also offers industry-leading Acceleration solutions that provide fast, agile, secure acceleration of any app, over any network, to users anywhere. Together with our thousands of market-leading customers globally – including 95% of the *FORTUNE* 100 – we are empowering next-generation digital experiences. Learn more at [riverbed.com](https://riverbed.com).